



AUSTRALIAN RAIL TRACK CORPORATION LTD

This document has been adopted by the ARTC with the permission of the NSW Government and will continue to apply under the authority of the ARTC General Manager Infrastructure, Strategy & Performance until further notice

Discipline
Engineering Standard – NSW

Category
Signalling

Title
Overlaps

Reference Number
SDS 04 – (RIC Standard: SC 00 13 01 04 SP)

Document Control

Status	Date	Prepared	Reviewed	Endorsed	Approved
Issue 1 Revision 2	Mar 05	Standards and Systems	Standards Engineer	GM Infrastructure Strategy & Performance	Safety Committee
		Refer to Reference Number	H Olsen	M Owens	Refer to minutes of meeting 12/08/04

DISCLAIMER

Australian Rail Track Corporation has used its best endeavors to ensure that the content, layout and text of this document is accurate, complete and suitable for its stated purpose. It makes no warranties, express or implied, that compliance with the contents of this document shall be sufficient to ensure safe systems of work or operation. Australian Rail Track Corporation will not be liable to pay compensation in respect of the content or subsequent use of this document for any other purpose than its stated purpose or for any purpose other than that for which it was prepared except where it can be shown to have acted in bad faith or there has been willful default.

DOCUMENT APPROVAL

The technical content of this document has been approved by the relevant ARTC engineering authority and has also been endorsed by the ARTC Safety Committee.

DOCUMENT SUPPLY and CONTROL

The Primary Version of this document is the electronic version that is available and accessible on the Australian Rail Track Corporation Internet and Intranet website.

It is the document user's sole responsibility to ensure that copies are checked for currency against the Primary Version prior to its use.

COPYRIGHT

The information in this document is Copyright protected. Apart from the reproduction without alteration of this document for personal use, non-profit purposes or for any fair dealing as permitted under the Copyright Act 1968, no part of this document may be reproduced, altered, stored or transmitted by any person without the prior written consent of ARTC.

About This Standard

This Principle addresses the concept of an overlap to provide a margin of safety between following trains and provides definition for of the terms associated with overlaps.

Document History

Primary Source – RIC Standard SC 00 13 01 04 SP Version 5.0

List of Amendments –

ISSUE	DATE	CLAUSE	DESCRIPTION
1.1	01/09/2004		<ul style="list-style-type: none">▪ Reformatting to ARTC Standard
1.2	14/03/2005	Disclaimer	<ul style="list-style-type: none">▪ Minor editorial change▪ Footer reformatted

Contents

4	Overlaps	7
4.1	Principle No. 4.1 - Overlaps Concepts & Definitions	7
4.1.1	Introduction	7
4.1.2	Overlap - Concept	7
4.1.3	Overlap - Definition	7
4.1.4	Overlap Distance	7
4.1.5	Overlap Track Circuit(s) - Definition	8
4.2	Principle No. 4.2 - Overlaps On Double Lines At Colour Light Running Signals Not Equipped With Train Stops	9
4.2.1	Introduction	9
4.2.2	Provision Of An Overlap	9
4.2.3	Overlap Distance	9
4.2.4	Variations to Overlap Distances	9
4.3	Principle No. 4.3 - Overlaps On Lines Above Ground In Trainstop Territory	10
4.3.1	Introduction	10
4.3.2	Provision Of An Overlap	10
4.3.3	Overlap Distance	10
4.3.4	Provision of An Overlap Track Circuit	10
4.3.5	Variation To Overlap Distances	10
4.3.6	Overlaps in Isolated Train Stop Fitted Areas	10
4.4	Principle No. 4.4 - Section Intentionally Left Blank	12
4.5	Principle No. 4.5 - Overlaps in CTC Territory	13
4.5.1	Introduction	13
4.5.2	Provision Of An Overlap On A Single Line	13
4.5.2.1	Requirements	13
4.5.2.2	Overlap Distance	14
4.5.2.3	Variations To Overlap Distances	14
4.5.3	Provision Of Overlaps At A Crossing Loop	14
4.5.3.1	Requirement	14
4.5.3.2	Overlap Distances	16
4.6	Principle No. 4.6 - Overlaps In ETS And OTS Territory Where Colour Light Running Signals Are Provided	17
4.6.1	Introduction	17
4.6.2	Provision Of An Overlap	17
4.6.3	Overlap Distance	17
4.7	Principle No. 4.7 - Conditional Overlaps	18
4.7.1	Introduction	18
4.7.2	Provision Of A Conditional Overlap	18
4.7.3	Requirements For A Conditional Overlap Permitting The Display Of A Conditional Caution Aspect	18
4.8	Principle No. 4.8- Locking Opposing Routes Leading Into Or Situated Within An Overlap	19
4.8.1	Introduction	19
4.8.2	Requirements For The Signal Requiring The Overlap	19
4.8.3	Requirements For Opposing Signals	20
4.9	Principle No. 4.9 - Setting And Locking Of Points Within An Overlap	21
4.9.1	Introduction	21

4.9.2	Trailing Points	21
4.9.3	Facing Points	22
4.9.4	Facing Points Providing Flank Protection	24
4.9.5	Special Arrangements.....	24
4.10	Principle No. 4.10 - Setting And Locking Of Points Within An Overlap At A Crossing Loop In CTC Territory	25
4.10.1	Introduction	25
4.10.2	Requirements For Home Signals.....	25
4.10.2.1	Where an Opposing Out Home Signal is not Provided	25
4.10.2.2	Where an Opposing Outer Home Signal is Provided	26
4.11	Principle No. 4.11 - Section Intentionally Left Blank	28
4.12	Principle No. 4.12 - Overlaps For Low Speed Subsidiary Signals In Colour Light Territory ..	28
4.12.1	Introduction	28
4.12.2	Requirement	28
4.13	Principle No. 4.13 - Overlaps For Subsidiary Or Ground Shunting Signals	29
4.13.1	Introduction	29
4.13.2	Requirement	29
4.14	Principle No. 4.14 – Preferential Setting of Conditionally Locked Points In An Overlap	30
4.14.1	Introduction	30
4.14.2	Purpose	30
4.14.3	Requirement	30
4.14.4	Control Tables	31
4.15	Principle No. 4.15 - Automatic Overlap Setting By Track Circuit Occupation	32
4.15.1	Introduction	32
4.15.2	Purpose	32
4.15.3	Requirements	32
4.15.4	Control Tables	33
4.16	Principle No. 4.16 - Overlap Swinging	34
4.16.1	Introduction	34
4.16.2	Purpose	34
4.16.3	Requirements	34
4.17	Principle No. 4.17 - Overlap Maintenance	35
4.17.1	Introduction	35
4.17.2	Purpose	35
4.17.3	Requirements	35
4.17.4	Control Tables	35

4 Overlaps

4.1 Principle No. 4.1 - Overlaps Concepts & Definitions

4.1.1 Introduction

This Principle addresses the concept of an overlap to provide a margin of safety between following trains and provides definition for of the terms associated with overlaps.

4.1.2 Overlap - Concept

Where provided the purpose of an overlap is to ensure a margin of safety beyond a stop signal by establishing a predetermined separation distance between two trains.

4.1.3 Overlap - Definition

An overlap is the section of track immediately in advance of a Stop signal, which must be unoccupied before the Stop signal next in rear is permitted to show a proceed indication.

4.1.4 Overlap Distance

The overlap distance is the length of the section of track which forms the overlap and is measured from the Stop signal to a predetermined clearing point in advance.

This predetermined clearing point may be prescribed under these Principles or measured dynamically resulting in sets of braking curves, or may be the result of a combination of both.

Factors which influence the predetermination of the clearing point may be

- Historical precedents and experimental data.
- Maximum Line Speed.
- Permanent Speed Restrictions.
- Service Speed.
- Service Braking Curves.
- Emergency Braking Curves.
- Impact of gradient.
- Emergency Brake Tripping System.
- Automatic Train Protection System.

- Provision of conditional caution aspect clearance of signals

4.1.5 Overlap Track Circuit(s) - Definition

One or more track circuits which constitute the predetermined overlap distance.

On plain line this will always be at least the “A” track circuit beyond a stop signal.

4.2 Principle No. 4.2 - Overlaps On Double Lines At Colour Light Running Signals Not Equipped With Train Stops.

4.2.1 Introduction

This Principle addresses the requirements for the provision of overlaps on double lines at running signals in colour light signalling territory which are not equipped with train stops.

4.2.2 Provision Of An Overlap

If a running signal on a passenger line is capable of showing an unconditional warning aspect then an overlap shall be provided immediately beyond the stop signal to which the warning aspect applies.

4.2.3 Overlap Distance

The nominal length of the overlap to be provided shall not be less than the minimum distances shown below.

Speed Range over Particular

Section of Line

Minimum Overlap Distance

0 - 59 Kph	300m (or longest braking distance, if less)
60 - 79 Kph	400m (or longest braking distance, if less)
80 Kph and greater	500m (or longest braking distance, if less)

4.2.4 Variations to Overlap Distances

If the grade on a particular section of line is greater than 1 in 100 falling then the overlap distance shall be increased for that speed range by not less than 100 metres.

If a block joint already exists or is to be provided for other purposes and could also be used as an overlap block joint without adversely affecting the line headway then the overlap distance may be increased to avoid the provision of a separate overlap track circuit.

If the line headway is adversely affected by the nominal overlap distance then a reduction in the overlap distance should be considered based on the appropriate factors presented under Principle No. 4.1.4.

Where train speeds are permanently restricted due to them departing yards or negotiating turnouts or junctions, then the overlaps beyond the signal may be reduced to 90 metres where the speed approaching the signal is restricted to 15kph and to 150 metres where the speed is restricted to 25kph, or reduced to the longest braking distance, if less.

If a running signal is more than 1.5 Km and more than 1.5 times service braking distance from the next signal then the overlap distance for that running signal beyond the next signal shall be commensurably greater than the normal minimum overlap distance.

4.3 Principle No. 4.3 - Overlaps On Lines Above Ground In Trainstop Territory

4.3.1 Introduction

This Principle addresses the requirements for the provision of overlaps on lines above ground at running signals in colour light signalling territory which are equipped with train stops.

4.3.2 Provision Of An Overlap

If a running signal on a passenger line is capable of showing an unconditional warning aspect then an overlap shall be provided immediately beyond the stop signal to which the warning aspect applies.

4.3.3 Overlap Distance

The length of the overlap shall be determined from the GE52A Trip Stop Braking Curve for R/S double deck suburban sets provided by the Principal Brake Engineer, State Rail for trains operating at the permissible line speed applicable to the particular section of line concerned. Refer to the Attachment.

If the service speed is less than line speed then it may be permissible to use the service speed for the determination of the overlap length, however effective arrangements must be in place to ensure tripfitted trains with higher service speeds and longer braking distances are not introduced to run on the line without a proper risk analysis.

4.3.4 Provision of An Overlap Track Circuit

Separate overlap track circuits shall be provided at least equal to the overlap distance determined under 4.3.3 above.

4.3.5 Variation To Overlap Distances

If the line headway is adversely affected by the overlap distance in a particular section then a reduction of the overlap distance should be investigated based on the appropriate factors presented under Principle No. 4.1.4

4.3.6 Overlaps in Isolated Train Stop Fitted Areas

It is permissible to install train stops in isolated areas where a safety benefit is to be realised, without necessarily adjusting existing overlaps. However, should significant work occur in these areas, overlap distances should be adjusted to conform to GE52A.

ATTACHMENT TO PRINCIPLE 4.3

Applicable Braking Curves For Overlaps On Particular Lines

Line	Braking Requirements (Overlaps)
1. Inner City	
City Railway/Waverton	GE52 * To include acceleration allowance
Erskineville – Bondi Junction	GE52 * To include acceleration allowance
Central – Strathfield	GE52A
Central – Meeks Road Junction (Tempe)	GE52A
Central – Wolli Creek (NSR)	GE52
2. Illawarra	
Meeks Road Junction – Helensburgh	GE52A
3. North	
Strathfield – Hawkesbury River	GE52A
Fassifern – Hamilton Junction	GE52A
Hamilton Junction – Newcastle	GE52A
4. West	
Strathfield – Emu Plains	GE52A
Flemington – Homebush Bay - Lidcombe	GE52A
Clyde – Carlingford	GE52A
Blacktown - Richmond	GE52A

5. South	
Lidcombe – Cabramatta (via Sefton)	GE52A
Granville – Cabramatta	GE52A

Tempe – Glenfield	GE52A
Cabramatta – Macarthur	GE52A
6. North Shore	
Waverton – Hornsby	GE52A
7. Bankstown	
Sefton Park Junction - Sydenham	GE52A

4.4 Principle No. 4.4 - Section Intentionally Left Blank

4.5 Principle No. 4.5 - Overlaps in CTC Territory

4.5.1 Introduction


This Principle addresses the requirements for the provision of overlaps on single lines and in crossing loops in C.T.C. colour light territory.

4.5.2 Provision Of An Overlap On A Single Line

4.5.2.1 Requirements


An overlap shall be provided at the exit from a single line block section immediately in advance of the home signal .

This overlap shall extend from the home signal as far as the opposing main and loop starting signals controlling the entrance to the single line block section and shall incorporate loop and flank protection. Refer to Principle 4.10. Refer to figure 1.



If for operational reasons an outer home signal is provided at the exit from a single line block section together with an opposing starting signal on the single line then an overlap shall be provided immediately in advance of the outer home signal.

This overlap shall extend from the outer home signal towards the opposing starting signal on the single line. Refer to figure 2.



4.5.2.2 Overlap Distance

If a home signal only is provided then a nominal overlap of 200m shall be provided for the single line block section extending over the loop end.

If main running signals are provided for loop entry, this distance shall be 300m. Refer to figure 1.

If an outer home signal is provided then a nominal overlap of 500m shall be provided for the single line block section and this shall abut a 100m overlap provided immediately in advance of the opposing starting signal. Refer to figure 2. and section 4.5.3 of this Principle.

4.5.2.3 Variations To Overlap Distances

If a block joint which already exists or is to be provided for other purposes could also be used as an overlap block joint without adversely affecting the line headway then the overlap distance may be increased to avoid the provision of a separate overlap track circuit.


4.5.3 Provision Of Overlaps At A Crossing Loop

4.5.3.1 Requirement

The home signal shall be provided with an overlap immediately in advance of the main and loop starting signals into the single line block section in advance.

This overlap shall extend from the main or loop starting signal into the single line block

section in advance as far as the opposing home signal. Refer to figure 3.




If a subsidiary shunt signal is fitted to a home signal then it shall be provided with an overlap immediately in advance of the main and loop starting signals into the single line block section in advance.

This overlap shall extend from the main or loop starting signals into the single line block section in advance towards the opposing home signal.

This overlap shall be a locking overlap only and no overlap track circuit control shall apply to the subsidiary shunt aspect.

If an outer home signal is provided then an overlap shall be provided for the caution aspect.

This overlap shall extend from the home signal to the main or loop signals leading into the single line block section in advance. Refer to figure 4



If a main or loop exit signal is fitted with a subsidiary shunt signal then the subsidiary shunt signal shall be provided with an overlap which extends towards the opposing outer home signal. Refer to figure 2.

This overlap shall be a locking overlap only and no overlap track circuit control shall apply to the subsidiary shunt aspect.

4.5.3.2 Overlap Distances

At CTC loops using low speed for entry, the distance between the loop and main starting signals and the home signal shall be 200m. where main running aspects are used for entry, this distance shall be 300m. The points shall be set to deflect any conflicting movement.

The nominal overlap distance for a subsidiary shunt signal shall be 100m.

The nominal overlap distance for an outer home signal shall not be less than that required under Principle No. 4.2 and not greater than the distance to the main and loop signals leading into the section in advance.

4.6 Principle No. 4.6 - Overlaps In ETS And OTS Territory Where Colour Light Running Signals Are Provided

4.6.1 Introduction

This Principle addresses the requirements for the provision of overlaps on single lines operated under electric train staff or ordinary train staff regulations and where colour light home and starting signals are provided.

4.6.2 Provision Of An Overlap

An overlap shall be provided at the exit from the single line section immediately in advance of the home signal.

This overlap shall extend from the home signal to the opposing starting signal or signals controlling the entrance to the single line section or approved clearing point as required. Refer to figure 1




FIGURE 1
OVERLAPS IN ETS OR OTS TERRITORY
PRINCIPLE N° 4.6

4.6.3 Overlap Distance

The length of the overlap shall be 200m minimum.

4.7 Principle No. 4.7 - Conditional Overlaps

4.7.1 Introduction


This Principle addresses the need to provide and the requirements for conditional overlaps in colour light signal territory.

4.7.2 Provision Of A Conditional Overlap

If it is necessary for specific operational purposes or for general headway reasons for trains to be brought closer together than is permitted by the requirements for a full overlap as described in Principles 4.2, 4.3 then a conditional overlap may be provided enabling a running signal to show a conditional caution aspect.

4.7.3 Requirements For A Conditional Overlap Permitting The Display Of A Conditional Caution Aspect

If a full overlap is not available, but an overlap of reduced distance is known to be clear and the train ahead occupying part of the full overlap distance is stationary or signalled away in the correct direction of running then the running signal requiring the full overlap shall be cleared after a suitable time delay has elapsed ensuring that the speed of the following train has been reduced to be commensurate with the safety margin provided by the reduced overlap distance. Refer to figure 1.



4.8 Principle No. 4.8 - Locking Opposing Routes Leading Into Or Situated Within An Overlap


4.8.1 Introduction

This Principle addresses the requirements for locking out opposing routes leading into or situated within an overlap by a particular route of the signal requiring the overlap.

4.8.2 Requirements For The Signal Requiring The Overlap

If a signal requires an overlap into which a route or overlap from an opposing signal leads or in which the route from an opposing signal is situated then the opposing route shall be normal and any associated track circuit holding released, if applicable, before the particular route of the signal requiring the overlap is permitted to set. Refer to figure 1.

If it is required to set the particular route of the signal requiring the overlap then the opposing routes leading into the overlap or situated within the overlap shall be locked normal until the particular route of the signal requiring the overlap is normalised and any associated track circuit holding released, if applicable. Refer to figure 1.



4.8.3 Requirements For Opposing Signals

If it is required to set a route from an opposing signal leading into or situated within an overlap then the particular route of the signal requiring the overlap shall be locked normal until the route from the opposing signal has been normalised and any associated track circuit holding released, if applicable.

4.9 Principle No. 4.9 - Setting And Locking Of Points Within An Overlap


4.9.1 Introduction

This Principle addresses the requirement for setting and locking of trailing and facing points when situated within an overlap and for trapping and flank protection to an overlap.


4.9.2 Trailing Points

If a set of trailing points situated within an overlap is available then it shall be set and locked in the appropriate position by the particular route of the signal requiring the overlap and remain locked until the particular route has been normalised or if provided an alternative overlap has been set.

If a train passes the signal requiring the overlap then the trailing points shall also become locked in position by track circuit occupancy until the train has come to a stand at the signal in advance and any time release provided has expired or the train has passed beyond the signal in advance and the trailing points have become directly locked by track circuit occupancy. Refer to figure 1.



If alternative overlaps are provided then a set of trailing points shall be set and locked as described above subject to the particular lay of the overlap. Refer to figure 2.



601 SET AND LOCKED NORMAL BY 99(M) AND HELD BY
 99AT OR 99BT OCCUPIED OR UNTIL 99BT OCCUPIED
 FOR t SECONDS IF 600 REVERSE

FIGURE 2


SETTING & LOCKING OF POINTS IN AN OVERLAP
 PRINCIPLE N° 4.9

If a set of trailing points situated within an overlap is not available then the particular route of the signal requiring the overlap shall be inhibited from setting.

4.9.3 Facing Points

If a set of facing points is situated within an overlap and each of the alternative overlaps is available then no setting or locking of the facing points is required. Refer to figure 3.

If a set of facing points is situated within an overlap and one of the alternative overlaps is not permitted or is not available then the facing points shall be set and locked in the direction of the available overlap by the particular route of the signal requiring the overlap and remain locked until the particular route has been normalised or until an alternative overlap has become available. Refer to figure 3.



If a train passes the signal requiring the overlap then the facing points shall remain locked in position, if required, by track circuit occupancy until the train has come to a stand at the signal in advance and any time release provided has expired or the train has passed beyond the signal in advance and the facing points have become directly locked by track circuit occupancy.

If a set of facing points situated within an overlap is not available to be set then the particular route of the signal requiring the overlap shall be inhibited from setting.

4.9.4 Facing Points Providing Flank Protection

If a set of facing points which provides flank protection to an overlap is available then it shall be set and locked in the appropriate position by the particular route of the signal requiring the overlap and remain locked until the particular route has been normalised or if provided an alternative overlap has been set.

If a train passes the signal requiring the overlap then the points shall also become locked in position by track circuit occupancy until the train has come to a stand at the signal in advance and any time release provided has expired or the train has passed beyond the signal in advance and the points have become directly locked by track circuit occupancy. Refer to figure 1.

If alternative overlaps are provided then a set of facing points providing flank protection shall be set and locked as described above subject to the particular lay of the overlap. Refer to figure 2.

If a set of facing points which provides flank protection to an overlap is not available then the particular route of the signal requiring the overlap shall be inhibited from setting.

4.9.5 Special Arrangements

Under certain circumstances it may be permissible to provide special arrangements for the setting of overlap conditions. For example the provision of dedicated push buttons to enable special arrangements to be invoked.

4.10 Principle No. 4.10 - Setting And Locking Of Points Within An Overlap At A Crossing Loop In CTC Territory


4.10.1 Introduction

This Principle addresses the requirements for setting and locking points situated within the various overlaps required for subsidiary low speed, shunt, and outer home signals at a crossing loop in CTC territory.

4.10.2 Requirements For Home Signals

4.10.2.1 Where an Opposing Outer Home Signal is not Provided


If the starting signal ahead is not clear and it is required to clear the low speed subsidiary signal fitted to the home signal for the main line then the particular route shall set and lock the trailing points in the overlap in the reverse position until the particular route is normalised. Refer to figure 1.



This locking shall not be held by the occupation of track circuits.

The points shall be detected reverse before the signal is permitted to clear and continuously thereafter.

If it is required to clear the home signal for the loop, then the particular route shall set and lock the trailing points in the overlap in the normal position until the particular route is normalised. Refer to figure 2.




This locking shall not be held by the occupation of track circuits.

The points shall be detected normal before the signal is permitted to clear and continuously thereafter.

4.10.2.2 Where an Opposing Outer Home Signal is Provided

If it is required to clear the low speed subsidiary signal fitted to the home signal for the main line or the loop and an opposing outer home signal is provided then the particular route required shall set and lock the trailing points in accordance with the requirements of Principle 4.9. Refer to figures 3 and 4.



This locking shall be held by the occupation of track circuits or released by track circuit occupation for a predetermined time.

4.11 Principle No. 4.11 - Section Intentionally Left Blank

4.12 Principle No. 4.12 - Overlaps For Low Speed Subsidiary Signals In Colour Light Territory

4.12.1 Introduction

This Principle addresses the requirements for the provision of a locking overlap for a movement made under the control of a low speed aspect on a running signal.

4.12.2 Requirement

A locking overlap coincidental with the caution overlap of the running signal with which the low speed signal is associated shall generally be provided.

Track circuits in the overlap shall be proved clear consistent with the low speed aspect to ensure that trains proceeding at low speed are afforded adequate protection.

Depending on circumstances governing the overlap conditions, consideration should be given to the provision of an intermediate trainstop for low speed movements.

Locking overlaps used with conditional low speed indications may be considered for reduction to meet special operations requirements on obtaining special approval.

4.13 Principle No. 4.13 - Overlaps For Subsidiary Or Ground Shunting Signals

4.13.1 Introduction

This Principle addresses the requirements for the provision of an locking overlap for a movement from a shunting signal in colour light territory and applies whether the shunt signal takes the form of a subsidiary on a running signal or a ground shunt.

4.13.2 Requirement

A nominal locking overlap of 100m on a running line shall be provided for a subsidiary shunting signal or ground shunting signal.

If necessary the shunt signal requiring the overlap shall set, lock and maintain one or more sets of points in the locking overlap to eliminate the possibility of converging or opposing movements obstructing the overlap once established.

Overlap track circuits shall not be proved clear in shunting signal aspects. Refer to Principle 1.20.

In yards, locking of ground frames in the overlap is not usually applied and locking in the overlap is usually via the signals, not the points, and is generally not maintained.

In yards where speeds are suitably restricted, the locking overlap distance may be reduced to 60m, or braking distance from the STOP signal if less.

In yards, for directly opposing movements between low speed shunt routes, the shared overlap may be reduced to three quarters of the combined distance of the individual overlaps, however the 60m minimum overlap (or braking distance overlap, if less) must be applied to any converging movements.

4.14 Principle No. 4.14 – Preferential Setting of Conditionally Locked Points In An Overlap

4.14.1 Introduction

This Principle addresses the requirements for the provision of preferential setting of conditionally locked points in an overlap.


4.14.2 Purpose

Preferential setting of facing points in an overlap is provided to ensure that whenever possible an overlap is set in the direction of the most frequently used route ahead of an inner signal.

This reduces the probability of an overlap being set in the least used direction which may result in excessive or unnecessary overlap swinging if other routes, when setting, interact with the established overlap.

4.14.3 Requirement

If an overlap contains a set of facing points that lead over a set of trailing points which are situated beyond the facing points, and the lay of the facing points is towards the trailing points and this is the most used direction of traffic and the trailing points are available to be set (or are already set) for the overlap then they shall be set (if necessary) and locked as applicable for the overlap. Refer to figure 1.



This lay of overlap shall be the first preference.

If the trailing points are not available to be set for the overlap then the facing points shall be set and locked in the opposite lay towards the alternative overlap which shall be the least used direction of traffic. Refer to figure 2.

This lay of overlap shall be the second preference.

4.14.4 Control Tables

These complimentary setting and locking conditions shall be placed in parenthesis and suffixed 1 and 2 to indicate the preference.

eg.	101 sets & locks points normal	(401N W 400 N) ¹
	101 sets & locks points reverse	(400R W 401 R) ²

Where 2 denotes "and not free".

4.15 Principle No. 4.15 - Automatic Overlap Setting By Track Circuit Occupation

4.15.1 Introduction


This Principle addresses the requirements for the provision of automatic overlap setting due to the occupation of track circuits in the alternative overlap at the time a route is set.

4.15.2 Purpose

This form of automatic overlap setting is provided when an outer running signal has a choice of two or more overlaps beyond an inner signal and due to track circuit occupation one of the overlaps is not available. Under these conditions the facing points may be set towards the available overlap automatically when the route is setting.

4.15.3 Requirements

If a choice of overlap exists beyond an inner signal at the time of setting an outer signal and the overlap in the direction in which the facing points are set is unavailable due to the occupation of track circuits then the outer signal may set and lock the facing points in the direction of the available overlap. Refer to figure 1.



101 SETS 601 N W 103XT OCC

101 SETS 601 R W 103BT OCC

FIGURE 1

AUTOMATIC OVERLAP SETTING
BY TRACK CIRCUIT OCCUPATION
PRINCIPLE N° 4.15

These arrangements may become overly complicated if two or three sets of facing points are involved and multiple overlap choices are available and care should be exercised to restrict the overlap swinging to the minimum to satisfy traffic conditions. Overlaps should not be swung across opposing roads.

4.15.4 Control Tables

Details of the overlap setting shall be shown on the Control Table points sheet concerned.

4.16 Principle No. 4.16 - Overlap Swinging

4.16.1 Introduction

This Principle addresses the requirements for the provision of overlap swinging facilities.

4.16.2 Purpose

Overlap swinging is provided to assist an operator to establish routes which will interact with one or more overlaps previously set for one or more routes. This avoids the operator from having to manually establish the alternative overlaps by individual point key movements before the route to be set becomes available. This may become a complex and time consuming operation where two or more junctions overlap and several routes have already been set.

4.16.3 Requirements

If one or more routes have already been set, the appropriate overlaps established and the signals are displaying proceed aspects and another route requires to be set which will alter the lay of one or more sets of points in the overlaps of the previously cleared signals then the route which is to be set shall adjust the lay of the established overlaps progressively and prove that an alternative overlap is available before the facing points leading towards the alternative overlap are reset to opposite lay.

If several sets of points are involved then this process of overlap swinging shall be enforced by the setting and locking of the overlap points in sequence.

Signals already displaying proceed aspects shall have their aspects maintained during the overlap swinging and shall prove the appropriate alternative overlap conditions when the overlap movement is complete.

4.17 Principle No. 4.17 - Overlap Maintenance

4.17.1 Introduction

This Principle addresses the requirements for the locking of facing points to ensure that a clear overlap is maintained while an alternative overlap is occupied and a route is set or a train is occupying the route leading up to the home signal at the points.

4.17.2 Purpose

This locking is provided when an outer running signal has a choice of two or more overlaps beyond an inner signal, and due to track circuit occupation, one (or more) of the overlaps is not available.

4.17.3 Requirements

If a choice of overlap exists beyond an inner signal, then the clearing of an outer signal will lock any facing points beyond the inner signal to prevent the operation of those points towards the obstructed overlap.

The points shall remain locked whenever a train is approaching the inner signal, and the alternative overlap remains obstructed.

This locking may be released when the alternative overlap becomes clear, or the route has been cancelled and the approach locking released, or the train has been time released at a stand at the inner signal.

If multiple overlaps exist, care should be exercised to ensure that overlap maintenance is properly applied through the various combinations of conditions.

4.17.4 Control Tables

Details of overlap maintenance locking shall be shown on the points sheet control table.

